One Year Limited Warranty

Hollywood Controls Inc ("the Company") warrants the HC1200EB PowerBlaster Strobe against defects in material or workmanship for one year from date of original purchase. The Company, at it's option, will repair or replace the components and return them to you free of charge.

This warranty is extended only to the original purchaser on record with the Company.

Your remedy is limited to this warranty policy. This warranty only covers product failure that occurs due to defects in material and workmanship occurring during the normal expected use of the product. It does not cover damage caused by accident, misuse, abuse, lack of reasonable care, alterations or improper installation.

There are no expressed warranties except as described above.

THE COMPANY SHALL NOT BE LI-ABLE FOR INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES RE-SULTING FROM THE USE OF THIS PRODUCT OR ARISING OUR OF ANY BREACH OF THIS WARRANTY, ALL IMPLIED WARRANTIES, IF ANY, IN-CLUDING IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO THE DU-RATION OF THIS FXPRFSS WAR-RANTY. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so

the above exclusions or limitations may not apply to you.

POWERBLASTER STROBE

No other warranty, written or verbal, is authorized by the Company. This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

For service during the warrantee period you must first contact the Company for an Return Merchandise Number (RMA) number. The Company will help you determine which part requires service and ask that you return that component ONLY. The Company, at it's option, will repair or replace the components and return them to you free of charge. All returned components must be accompanied by a RMA number issued by the Company and be returned by insured prepaid freight. Products returned without a Company issued RMA will not be accepted. The Company is not responsible for merchandise damaged in transit. Evident or concealed damage made in transit should be reported at once to the delivery carrier and a claim filed with them.

The Company reserves the right to change or modify the operation, design, components and description of this system without notice.

HOLLYWOOD CONTROLS INC.



Phone:

Toll-free: 888-318-2380

sales@hollywoodcontrols.com

© 2013 Hollywood Controls Inc 01/13 R2

PowerBlaster Strobe

Model: HC1200EB Eliminator 70W PowerBlaster Strobe With Built-in RCA Triggering Input





General Description

The HC1200EB is a unique, logic triggered, powerful strobe unit that can be synchronized to the HC1410/14/17 PowerBlaster systems.

This Strobe has three modes of triggering:

- RCA interfaced external triggering compatible with the Hollywood Controls triggering systems.
- Automatic triggering with a variable flash rate set by the dial knob.
- 1/4" mono-cable daisy-chain trigger linking using the IN/OUT jacks. (Not compatible with Hollywood Controls triggering)

Features:

2

- · Industrial Quality
- Very Rugged
- RCA Plug Interface
- · 1/4" Cable Slave Linking

Index:

Safety Precautions

General Description

Warrantee

Back Panel Interface

The *MODE switch* on the back of the strobe selects one of two operating conditions:

<u>UP</u> -RCA/¼" Jacks: External triggering on both.

<u>Down</u> -AutoSpeed/ $\frac{1}{4}$ " Jacks: External triggering on $\frac{1}{4}$ " jacks and automatic internal triggering with speed adjustment.

The RCA mode must be selected for triggerina from our PowerBlaster equipment.

Slave Operation

It is possible to trigger more than one strobe from the same piece of equipment. To do this, the first strobe is set to use RCA triggering directly from the PowerBlaster equipment. The second strobe is set for 1/4" cable triggering and the connection is made from the MASTER-OUT of the first strobe to the SLAVE-IN of the second unit.

To test the HC1200EB Eliminator strobe function, unplug any 1/4" link plugs or RCA plugs and the strobe should begin flashing in AutoSpeed mode. Replace lamp or service the unit if it fails to operate.

Please read the enclosed Eliminator operating and safety instructions completely.

Safety Precautions

- DO NOT alter or remove labels.
- Keep dry.
- DO NOT connect to devices supplying power to the RCA plug.

One Year Limited Warranty

Hollywood Controls Inc ("the Company") warrants the HC1200EB PowerBlaster Strobe against defects in material or workmanship for one year from date of original purchase. The Company, at it's option, will repair or replace the components and return them to you free of charge.

This warranty is extended only to the original purchaser on record with the Company.

Your remedy is limited to this warranty policy. This warranty only covers product failure that occurs due to defects in material and workmanship occurring during the normal expected use of the product. It does not cover damage caused by accident, misuse, abuse, lack of reasonable care, alterations or improper installation.

There are no expressed warranties except as described above.

THE COMPANY SHALL NOT BE LI-ABLE FOR INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES RE-SULTING FROM THE USE OF THIS PRODUCT OR ARISING OUR OF ANY BREACH OF THIS WARRANTY, ALL IMPLIED WARRANTIES, IF ANY, IN-CLUDING IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO THE DU-RATION OF THIS FXPRFSS WAR-RANTY. Some states do not allow the exclusion or limitation of incidental or consequential damages, or limitations on how long an implied warranty lasts, so

the above exclusions or limitations may not apply to you.

No other warranty, written or verbal, is authorized by the Company. This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

For service during the warrantee period you must first contact the Company for an Return Merchandise Number (RMA) number. The Company will help you determine which part requires service and ask that you return that component ONLY. The Company, at it's option, will repair or replace the components and return them to you free of charge. All returned components must be accompanied by a RMA number issued by the Company and be returned by insured prepaid freight. Products returned without a Company issued RMA will not be accepted. The Company is not responsible for merchandise damaged in transit. Evident or concealed damage made in transit should be reported at once to the delivery carrier and a claim filed with them.

The Company reserves the right to change or modify the operation, design, components and description of this system without notice.

HOLLYWOOD CONTROLS INC.

Sedona, AZ 86351

Phone:

Toll-free: 888-318-2380

sales@hollywoodcontrols.com

© 2013 Hollywood Controls Inc 01/13 R2

Hollywood Controls Inc.

PowerBlaster Strobe

Model: HC1200EB Eliminator 70W PowerBlaster Strobe With Built-in RCA Triggering Input





General Description

The HC1200EB is a unique, logic triggered, powerful strobe unit that can be synchronized to the HC1410/14/17 PowerBlaster systems.

This Strobe has three modes of triggering:

- RCA interfaced external triggering compatible with the Hollywood Controls triggering systems.
- Automatic triggering with a variable flash rate set by the dial knob.
- 1/4" mono-cable daisy-chain trigger linking using the IN/OUT jacks. (Not compatible with Hollywood Controls triggering)

Features:

- Industrial Quality
- Very Rugged
- RCA Plug Interface
- I/4" Cable Slave Linking

Index:

Safety Precautions General Description 2

Warrantee

Back Panel Interface

The MODE switch on the back of the strobe selects one of two operating conditions:

UP -RCA/4" Jacks: External triggering on both.

Down - Auto Speed / 1/4" Jacks: External triagering on $\frac{1}{4}$ " jacks and automatic internal triggering with speed adjustment.

The RCA mode must be selected for triggering from our PowerBlaster equipment.

Slave Operation

It is possible to trigger more than one strobe from the same piece of equipment. To do this, the first strobe is set to use RCA triggering directly from the PowerBlaster equipment. The second strobe is set for 1/4" cable triggering and the connection is made from the MASTER-OUT of the first strobe to the SLAVF-IN of the second unit.

To test the HC1200EB Eliminator strobe function, unplug any 1/4" link plugs or RCA plugs and the strobe should begin flashing in AutoSpeed mode. Replace lamp or service the unit if it fails to operate.

Please read the enclosed Eliminator operating and safety instructions completely.

Safety Precautions

- DO NOT alter or remove labels
- Keep dry.
- DO NOT connect to devices supplying power to the RCA plug.